

L4 ANSWER 10 OF 561 CA COPYRIGHT 2004 ACS on STN
 AN 140:6222 CA
 ED Entered STN: 25 Dec 2003
 TI Water-soluble fireproofing composition with good elasticity and
 adhesion to substrates
 IN Masini, Giovanni
 PA Italy
 SO Ital., 10 pp.
 CODEN: ITXXBY
 DT Patent
 LA Italian
 IC ICM C09D
 CC 42-7 (Coatings, Inks, and Related Products)
 Section cross-reference(s): 55

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	IT 1311962	B1	20020320	IT 1999-GE130	19991104
PRAI	IT 1999-GE130		19991104		

AB The coating compn. with high adhesion to ferrous materials comprises 35-45
 parts inorg. inert compd., 25-35 parts pozzolan cement, 18-20
 parts hydrated alumina, 0 - 5 parts titania, 02 parts
 Al silicate, 3-3.5 parts film forming agent, 0.03-0.08 parts fluidizing
 agent, 0.10-0.20 rosin soap, 0.05 - 0.15 parts stabilizer, and at least
 30% water. The inorg. inert compd. is selected from CaCO₃,
 quartz flour, or powd. minerals, the film forming agent is selected from
 styrene-acrylic resins and ethylene-vinyl acetate copolymer, and the
 stabilizer is selected from starch and carboxymethylated starch.
 ST fireproofing coating high solids calcium carbonate acrylic binder;
 pozzolan cement alumina silicate EVA binder fireproofing
 coating; metal fireproofing waterborne coating adhesion elasticity
 IT Coating materials
 (fire-resistant; high-inorg. solids water-sol. fire-resistan